

**TEMPERATURE-TABLE for PTCR**  
**Higher quality products and lower costs through improved, reliable firing control**

Type PTCR - LTH	:		Ring Colour	:	Red
Ferro No.	:	1400604	Dimensions	:	± 20 x 10 x 7,0 mm
Temperature Range °C	:	970 - 1250°C			

Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature
mm	°C	mm	°C	mm	°C	mm	°C	mm	°C	mm	°C
				19,30	1199 °	19,80	1105 °				
				19,31	1198 °	19,81	1102 °				
				19,32	1197 °	19,82	1099 °				
				19,33	1195 °	19,83	1095 °				
				19,34	1194 °	19,84	1092 °				
				19,35	1193 °	19,85	1088 °				
				19,36	1191 °	19,86	1085 °				
				19,37	1190 °	19,87	1081 °				
				19,38	1189 °	19,88	1077 °				
				19,39	1187 °	19,89	1074 °				
				19,40	1186 °	19,90	1070 °				
				19,41	1185 °	19,91	1066 °				
				19,42	1183 °	19,92	1061 °				
				19,43	1182 °	19,93	1057 °				
				19,44	1181 °	19,94	1053 °				
				19,45	1179 °	19,95	1049 °				
		18,97	1250 °	19,46	1178 °	19,96	1044 °				
		18,98	1248 °	19,47	1176 °	19,97	1039 °				
		18,99	1246 °	19,48	1175 °	19,98	1035 °				
				19,49	1173 °	19,99	1030 °				
		19,00	1244 °	19,50	1172 °	20,00	1025 °				
		19,01	1242 °	19,51	1170 °	20,01	1020 °				
		19,02	1240 °	19,52	1169 °	20,02	1015 °				
		19,03	1239 °	19,53	1167 °	20,03	1009 °				
		19,04	1237 °	19,54	1165 °	20,04	1004 °				
		19,05	1235 °	19,55	1164 °	20,05	998 °				
		19,06	1233 °	19,56	1162 °	20,06	993 °				
		19,07	1232 °	19,57	1160 °	20,07	987 °				
		19,08	1230 °	19,58	1158 °	20,08	981 °				
		19,09	1228 °	19,59	1156 °	20,09	975 °				
		19,10	1227 °	19,60	1155 °	20,10	969 °				
		19,11	1225 °	19,61	1153 °						
		19,12	1224 °	19,62	1151 °						
		19,13	1222 °	19,63	1149 °						
		19,14	1221 °	19,64	1146 °						
		19,15	1219 °	19,65	1144 °						
		19,16	1218 °	19,66	1142 °						
		19,17	1216 °	19,67	1140 °						
		19,18	1215 °	19,68	1138 °						
		19,19	1213 °	19,69	1135 °						
		19,20	1212 °	19,70	1133 °						
		19,21	1211 °	19,71	1130 °						
		19,22	1209 °	19,72	1128 °						
		19,23	1208 °	19,73	1125 °						
		19,24	1207 °	19,74	1123 °						
		19,25	1205 °	19,75	1120 °						
		19,26	1204 °	19,76	1117 °						
		19,27	1203 °	19,77	1114 °						
		19,28	1202 °	19,78	1111 °						
		19,29	1200 °	19,79	1108 °						

Powder Batch #	:	163	Batch approved	:	
Date	:	04.02.2020	Quality Inspection	:	

For inquiries :  
 Customer Service Desk  
 Phone : +49 69 27116 432  
 Fax : +49 69 27116 243



**TEMPERATURE-TABLE for PTCR**  
**Higher quality products and lower costs through improved, reliable firing control**

Type PTCR - LTH	:		Ring Colour	:	Red
Ferro No.	:	1400604	Dimensions	:	± 20 x 10 x 7,0 mm
Temperature Range °F	:	1778 - 2282°F			

Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature
mm	°F	mm	°F	mm	°F	mm	°F	mm	°F	mm	°F
				19,30	2190 °	19,80	2021 °				
				19,31	2188 °	19,81	2015 °				
				19,32	2186 °	19,82	2010 °				
				19,33	2183 °	19,83	2004 °				
				19,34	2181 °	19,84	1997 °				
				19,35	2179 °	19,85	1991 °				
				19,36	2176 °	19,86	1985 °				
				19,37	2174 °	19,87	1978 °				
				19,38	2172 °	19,88	1971 °				
				19,39	2169 °	19,89	1964 °				
				19,40	2167 °	19,90	1957 °				
				19,41	2165 °	19,91	1950 °				
				19,42	2162 °	19,92	1943 °				
				19,43	2160 °	19,93	1935 °				
				19,44	2157 °	19,94	1927 °				
				19,45	2155 °	19,95	1919 °				
		18,97	2283 °	19,46	2152 °	19,96	1911 °				
		18,98	2279 °	19,47	2149 °	19,97	1903 °				
		18,99	2275 °	19,48	2147 °	19,98	1894 °				
				19,49	2144 °	19,99	1886 °				
		19,00	2272 °	19,50	2141 °	20,00	1877 °				
		19,01	2268 °	19,51	2138 °	20,01	1868 °				
		19,02	2265 °	19,52	2135 °	20,02	1858 °				
		19,03	2262 °	19,53	2133 °	20,03	1849 °				
		19,04	2258 °	19,54	2130 °	20,04	1839 °				
		19,05	2255 °	19,55	2126 °	20,05	1829 °				
		19,06	2252 °	19,56	2123 °	20,06	1819 °				
		19,07	2249 °	19,57	2120 °	20,07	1809 °				
		19,08	2246 °	19,58	2117 °	20,08	1798 °				
		19,09	2243 °	19,59	2114 °	20,09	1787 °				
		19,10	2240 °	19,60	2110 °	20,10	1776 °				
		19,11	2237 °	19,61	2107 °						
		19,12	2234 °	19,62	2103 °						
		19,13	2232 °	19,63	2099 °						
		19,14	2229 °	19,64	2096 °						
		19,15	2226 °	19,65	2092 °						
		19,16	2224 °	19,66	2088 °						
		19,17	2221 °	19,67	2084 °						
		19,18	2219 °	19,68	2080 °						
		19,19	2216 °	19,69	2075 °						
		19,20	2214 °	19,70	2071 °						
		19,21	2211 °	19,71	2067 °						
		19,22	2209 °	19,72	2062 °						
		19,23	2207 °	19,73	2057 °						
		19,24	2204 °	19,74	2053 °						
		19,25	2202 °	19,75	2048 °						
		19,26	2200 °	19,76	2043 °						
		19,27	2197 °	19,77	2037 °						
		19,28	2195 °	19,78	2032 °						
		19,29	2193 °	19,79	2027 °						

Powder Batch #	:	163	Batch approved
Date	:	04.02.2020	Quality Inspection :

For inquiries :  
 Customer Service Desk  
 Phone : +49 69 27116 432  
 Fax : +49 69 27116 243



