



Similar to illustration

### Frontloader KE 480 N

⊕	Volume	<b>480 litres</b>
⊙	Int. dimensions (w x d x h)	<b>640 x 770 x 980 mm</b>
Ⓢ	Power	<b>22 kW</b>
Ⓒ	Tanw *	<b>1240°C</b>

\* **Application temperature** for long-term and continuous use.

## Technical data

### ☰ Overview

Product group	<b>Kiln</b>
Design	<b>Frontloader</b>
Type	<b>KE-N series</b>

### Ⓢ Energy

Energy type	<b>Electrical</b>
Power	<b>22 kW</b>
Supply	<b>32 A</b>
Voltage	<b>400V</b>
Connection	<b>CEE 32 A</b>


### ⊕ Dimensions

Volume	<b>480 litres</b>
Int. dimensions (w x d x h)	<b>640 x 770 x 980 mm</b>
Ext. dimensions (W x D x H)	<b>980 x 1340 x 1830 mm</b>
Weight	<b>641 kg</b>

### ☆ Equipment

Insulation	<b>3-layer</b>
Heating	<b>5-side</b>
Heating elements	<b>Recessed into bricks</b>
Control	<b>TC 304</b>

## Besondere Merkmale



### **Long-term application temperature Tapp 1240°C**

The kiln is designed for long-term and continuous use at temperatures up to 1240°C which makes it suitable for applications such as bisque, earthenware, onglaze and stoneware firings. These applications correspond to Seger Cone 6a or Orton Cone 6.