



Similar to illustration

Toploader TE 35 Q

⊕	Volume	35 litres
⊙	Int. dimensions (w x d x h)	380 x 380 x 230 mm
⊞	Power	3.6 kW

Technical data

☰ Overview

Product group	Kiln
Design	Toploader
Type	TE-Q series

⏻ Energy

Energy type	Electrical
Power	3.6 kW
Supply	16 A
Voltage	230V
Connection	Schuko connector


⊕ Dimensions

Volume	35 litres
Int. dimensions (w x d x h)	380 x 380 x 230 mm
Ext. dimensions (W x D x H)	630 x 780 x 570 mm
Weight	81 kg

☆ Equipment

Insulation	2-layer
Heating	4-side
Heating elements	Recessed into bricks
Control	TC 304

Besondere Merkmale



Long-term application temperature Tapp 1290°C

The kiln is designed for long-term and continuous use at temperatures up to 1290°C which makes it suitable for applications such as bisque, earthenware, onglaze and stoneware firing as well as high-temperature stoneware, soft paste porcelain firings. These applications correspond to Seger Cone 8 or Orton Cone 9.



Power supply with 230 V "Schuko" plug connector

The high-quality insulation allows the kiln to be fired safely at stoneware temperatures using a regular 230 V "Schuko" plug connector (3.6 kW).




Gas pressure spring-supported opening mechanism for the lid

The sturdy lid construction is supported by gas pressure springs that allow easy, effortless and safe opening of the lid.



Integrated safety due to safety switch

A door contact switch automatically isolates the heating elements from the power supply when the kiln opens. The integrated overtemperature protection prevents damage to electrical components.



3-year warranty

We produce each kiln by hand and keep to strict quality guidelines. Therefore, we offer a voluntary 36-months warranty to extend legal warranty regulations.