

EPK Kaolin



Distributed by:
 Laguna Clay Company
 14400 Lomitas Ave
 City of Industry, CA 91746
 1-800-4Laguna
 info@lagunaclay.com
 www.lagunaclay.com

EPK Kaolin is a unique, high quality water washed ceramic kaolin which offers very white fired color, unusually good forming characteristics and high green strength. In glaze, EPK offers excellent suspension capabilities and uncommon cleanliness.

June 2011
 ©IMERYS Minerals Ltd 2011

Second Edition

TYPICAL PROPERTIES

CHEMICAL ANALYSIS

SiO ₂	(%)	45.7
Al ₂ O ₃	(%)	37.4
Fe ₂ O ₃	(%)	0.79
TiO ₂	(%)	0.37
P ₂ O ₅	(%)	0.24
K ₂ O	(%)	0.33
Na ₂ O	(%)	0.06
CaO	(%)	0.18
MgO	(%)	0.10
LOI.	(%)	13.9

TYPICAL VALUES

Moisture	(%)	
	Plus 325 Mesh (Pellet/Prill)	3.0
	Plus 325 Mesh (Airfloated)	1.0
Bulk Density	(lb/ft ³)	
	Loose	32
	Packed	46
Dry M.O.R.	(psi)	300
pH		6
M.B.I.	(meq/100g)	3.7
Surface Area	(m ² /g)	25.6
Average Particle Size	(µm)	1.0
325 Mesh Screen Residue	(%)	
	Pellet (Prill)	1.6
	Airfloated	1.2

** Soluble SO₂ (ppm)
 Low - Trace to 150
 Med - 150 to 450

Production Site
 Edgar Plant
 Country Road 20A
 Edgar, FL 32149
 United States
 Tel: +1 352 481 2421
 Fax: +1 352 481 2334

Commercial Office
 IMERYS Minerals
 100 Mansell Court East
 Suite 300
 Roswell, GA 30076
 United States
 Tel: +1 770 594 0660
 Fax: +1 770 645 3460
 Customer Service Number:
 Tel: +1 800 458 2529

The data quoted are determined by the use of Imerys Standard Test Methods, copies of which will be supplied on request. Every precaution is taken in production to ensure the products conform to our published data. Since the products are based on naturally occurring materials, we reserve the right to change these data should it become necessary. Sales are in accordance with our "Conditions of Sale", copies of which will be supplied upon request.