

# NICKEL OXIDE

Safety Data Sheet accordingtoRegulation(EC)No.1907/2006(REACH) &1272/2008 (CLP)Dateofissue:22/12/2010Revisiondate:12/12/2012

# SECTION 1: Identification of the substance/mixture and of the company/undertaking.

## **1.1. Product identifier**

Product name : Nickel Oxide EC No : 215-215-7/234-323-5 CAS No. : 1313-99-1/11099-02-8 REACH registration No. : 01-2119467172-41-XXXX Synonyms : nickel oxide sinter 75, NOS75, Nickel oxide (NiO), FMW, green nickel oxide, black nickel oxide,

mononickel oxide, nickel monoxide, nickelous oxide, nickel (II) oxide, nickel (2+) oxide, Bunsenite.

#### **1.2.** Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1.Relevantidentifieduses

Industrial use of powdered and shaped nickel oxide containing catalysts (A) Industrial use of nickel oxide-containing catalysts for the production of catalysts containing other nickel compounds Production of nickel base powders from nickel oxide Production of nickel-containing electronics and thermally functioning ceramics Production of nickel-containing enamel frits Production of nickel-containing pigments Production of nickel-containing glass Stainless, special steels and special alloys manufacturing

## 1.2.2.Usesadvised against

□None Full text of use descriptors: see section 16. Exposure Scenarios: Annex 1

## 1.3. Details of the supplier of the safety data sheet

Keramikos Oudeweg 153 2031 CC Haarlem



SDS Ref:- 12-12-2014

# NICKEL OXIDE Safety

## **Data Sheet**

according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012

#### 1.4. Emergency telephone number

023 - 542 44 16

### **SECTION 2: Hazards identification.**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]Skin SensitisationCategory 1CarcinogenicityCategory 1A; Specific Target Organ Toxicity, Repeated exposure – Category 1Aquatic ChronicCategory 4Full text of H-phrases: see section 16

#### Classification according to Directive 67/548/EEC or 1999/45/EC

Carcinogenicity Category 1; R49 T; R48/23 R43 R53 Full text of R-phrases: see section 16



Product identifier: Nickel Oxide Symbols: GHS07 – Exclamation mark GHS08 – Health Hazard Signal word (CLP): DANGER **Hazard statements** (CLP) : H317: May cause an allergic skin reaction H350: May cause cancer H372: Causes damage to organs through prolonged or repeated exposure

H413: May cause long lasting harmful effects to aquatic life

**Precautionary statements (CLP): NOTE:** number of P-statements has been reduced, as per CLP regulation, the full list can be found in Section 15)



P202: Do not handle until all safety precautions have been read and understood. P261: Avoid breathing dust/fume/ gas/mist/vapours/spray. [As modified by IV ATP] P273: Avoid release to the environment.

P281 – Use personal protective equipment as required.

P302 + P352: IF ON SKIN: Wash with plenty of water/... [As modified by IV ATP]

P501 – Dispose of contents and container in accordance with all local, regional, national and international regulations.

SDS Ref:- 12-12-2014

# **NICKEL OXIDE**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012

Full text of R-Statements and Precautionary statements see section 15

# SECTION 3: Composition/information on ingredients.

#### 3.1. Substances

Hazardous Ingredients	Typical Composition (%)	C.A.S. Number	EINECS/EC Label No.
Nickel Oxide NiO)	98	1313-99-1	215-215-7
Cobatous Oxide (CoO)	0-1.5	1307-96-6	215-154-6
Nickel Hydroxide	0-0.5	12054-48-7	235-008-05

## SECTION 4: First aid measures.

Ingestion: No specific first aid required.

Inhalation: No specific first aid required.

Skin: Remove contaminated clothing, and wash affected areas thoroughly with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Show label if possible.

Eyes: Irrigate eyeball thoroughly with water for at least 10 minutes. If discomfort persists seek medical attention.

## 4.2. Most important symptoms and effects, both acute and

delayed Skin contact: Rash Eye contact: Redness

## 4.3. Indication of any immediate medical attention and special treatment needed

No special requirements

# SECTION 5: Firefighting measures.

#### 5.1. Extinguishing media

Suitable extinguishing media: Any type to be selected according to materials stored in the immediate neighbourhood.



#### Unsuitable extinguishing media: None.

#### 5.2. Special hazards arising from the substance or mixture

Non-flammable. Extinguish surrounding fires with appropriate methods.

#### 5.3. Advice for firefighters

**Protection during firefighting:** Use of approved supplied air or self-contained breathing apparatus operated in positive pressure mode are satisfactory. Totally impervious protective suits, gloves, and boots must be worn.

SDS Ref:- 12-12-2014

NICKEL OXIDE

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012

## **SECTION 6: Accidental release measures.**

#### 6.1. Personal precautions, protective equipment and emergency procedures

**General measures:** Keep public away from danger area. See section 8.2. Avoid dust production. Avoid all contact with this substance.

**6.1.1. For non-emergency personnel** No additional information available **6.1.2. For emergency responders** No additional information available

#### **6.2. Environmental precautions**

Prevent entry to sewers and soil. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Collect mechanically and transfer into appropriate container for disposal. Avoid dust production.

#### 6.4. Reference to other sections

See section 8 and 13 for more information.

# SECTION 7: Handling and storage.

#### 7.1. Precautions for safe handling

**Precautions for safe handling:** Do not breathe dust. Avoid all contact with this substance Wash hands plentifully and other exposed areas with water after handling. Remove contaminated clothing and shoes. Wash clothing before reusing.



**Packagings:** Even those that have been emptied, will retain product residue. Always obey safety warnings and handle empty packagings as if they were full. Avoid all contact with this substance.

**Hygiene measures:** When using do not eat, drink or smoke. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Remove contaminated clothing and shoes.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in dry, cool, well-ventilated area. Keep away from food, drink and animal feeding stuffs. **Incompatible products:** None known

#### 7.3. Specific end use(s)

No additional information available

SDS Ref:- 12-12-2014

# NICKELOXIDE

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012

## SECTION 8: Exposure controls/personal protection.

#### **8.1. Exposure Limits.**

Nickel Oxide (NiO) - CAS 1313-39-1				
	Exposure Limit (mg/m <sup>3</sup> )	Year		
ACGIH TLV-TWA <sup>1</sup>	0.2* ‡ as Ni	2008		
OK WEL <sup>2</sup>	0.5 as Ni	2006		
Japan	1 as Ni	2012		
Korea	0.1 as Ni	2006		
China	1 as Ni	2007		

\* Inhalable fraction

‡ Insoluble inorganic fraction

#### **8.2. Environmental Limits.**

#### PNEC's

Compartment Unit PNEC
-----------------------



Freshwater	µg Ni/L (bioavailable)	3.55		
Marine	µg Ni/L	8.6		
Terrestrial	Mg Ni/kg	29.9		
DNEL's				
Compartment	Unit	PNEC		
Dermal				
Acute systemic	mg/Ni/kg/day	-		
Acute local	mg/Ni/cm²/day	_		
Long-term systemic	mg/Ni/kg/day	-		
Long-term local	mg/Ni/cm²/day	0.024		
Inhalation				
Acute systemic	mg/Ni/m <sup>3</sup>	520		
Acute local	mg/Ni/m <sup>3</sup>	3.9 <sup>1</sup>		
Long-term systemic	mg/Ni/m <sup>3</sup>	0.05 <sup>2 3</sup>		
Long-term local	mg/Ni/m³	0.05 <sup>2 3</sup>		

 $_{^1}$  Based on MMAD of 2.9µm, increases with increasing MMAD (estiamated as ≥6.4 mg

Ni/m<sup>3</sup> for Exposures to particles with a MMAD of  $\geq$  30µm.

 $<sup>^{</sup>_2}$  When handling powders of particle aerodynamic equivalent diameter (AED) below 10  $\mu m,$ 

exposures (8h TWA) to these powders should be kept under 0.01 mg.Ni/m $^3$ 

<sup>&</sup>lt;sup>3</sup> When exposure are solely to metallic and nickel oxides (without exposure to any other nickel compounds) and the

mean particle size of the aerosol is greater than 10µm AED ( $\leq$  10% of aerosol mass in respirable fraction), inhalable exposure levels uo to 0.2 mg Ni/m<sup>3</sup>could be reasonably assumed to be safe.



# NICKELOXIDE SafetyDataSheet

according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012

## 8.3. Occupational Exposure controls

**Appropriate engineering controls:** Use as far as possible in a closed system. Provide a regular control of the atmosphere. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Local exhaust and general ventilation must be adequate to meet exposure standards. Please refer to the annex (exposure scenarios).

**Hand protection:** Use gloves resistant to chemical products corresponding to EN 374:3. Take advice to gloves' supplier.

Eye protection: Wear safety glasses with side shields according EN 166.

Skinandbody protection: Wear closed protective clothing.

**Respiratory protection:** Use respiratory protection mask according to EN 140 or EN 405 with filter type P3 according to EN 143:2000 or FFP3 according to EN 149:2001.

Environmental exposurecontrols: Prevent entry to sewers and soil.

SECTION9:Physicalandchemical;properties.



Physical state at 20°C and 101.3 kPa Colour Odour Odour threshold pН Relative evaporation rate (butylacetate=1) Melting point Freezing point Boiling point Flash point Self ignition temperature Decomposition temperature Flammability (solid, gas) Vapour pressure Relative density Density Solubility in water **Bulk Density** 

Viscosity, kinematic Viscosity, dynamic Explosive properties Oxidising properties Explosive limits Granulometry

# **9.2. Other information** None

Solid White, green or black. odourless. Not applicable No data available No data available >1,900°C No data available Not applicable Not flammable >400°C No data available Not flammable Not applicable 6.75 g/cm<sup>3</sup> at 20<sup>0</sup>C No data available 3.52X10<sup>-5</sup> g/l at 20<sup>o</sup>C (green nickel oxide) 2.26X10<sup>-3</sup> g/l at 20°C (black nickel oxide) 800 - 1,300 kg/m<sup>3</sup> Not applicable No data available No data available Non-

No data available Nonoxidisng Not applicable <0.1% of particles aith a diameter <100µm

SDS Ref:- 12-12-2014

NICKEL OXIDE Safety Data Sheet accordingtoRegulation(EC)No.1907/2006(REACH) &1272/2008 (CLP)Dateofissue:22/12/2010Revisiondate:12/12/2012

# SECTION10:Stabilityandreactivity.

#### 10.1. Reactivity

Stable under normal conditions of handling and storage.

#### 10.2. Chemical stability

Stable under normal conditions of handling and storage.

6



Stable under normal conditions of handling and storage. **10.4. Conditions to avoid** Protect from moisture **10.5. Incompatible materials** None **10.6. Hazardous decomposition products** No information available

# SECTION11:Toxicologicalinformation.

#### 11.1. Information on toxicological effects

As a mixture the toxicological properties of the product are unknown. The toxicology of the reported ingredients are summarised below.

## **NickelOxide**

#### AcuteToxicity

a)Oral: Non toxic – LD50 ORAL RAT >11,000mg/kg (green); 9,990 (black)
b)Inhalation: Non toxic –LD50 INHAL RAT >5.08mg/kg (green); >5.15 (black)
C) Dermal: No information available

#### **Corrosivity/Irritation**

a)Respiratory Tract: No classificationb)Skin: Not corrosive/irritatingc) Eyes: Mildly irritating

## Sensitization

a)Respiratory Tract: Nickel metal induced asthma is very rare.3 case reports are available; the data is not sufficient to conclude that nickel metal is classified as a respiratory sensitizer.

b)Skin: Nickel oxide is currently classified as a dermal sensitizer (R43) according to the 1<sup>st</sup> ATP to the CLP Regulation. Recent studies evaluating the bioaccessibility of a series of Ni compounds in synthetic sweat indicated very low nickel ion release from Ni oxide, suggesting very low or no sensitization potency. Early Guinea pig maximization and Beuhler test results show low potential for nickel oxide to act as a dermal sensitizer.

SDS Ref:- 12-12-2014



# NICKEL OXIDE Safety Data Sheet

c) Pre-existing conditions: Individuals known to be allergic to nickel should avoid contact with nickel whenever possible to reduce the likelihood of nickel allergic dermatitis reactions (skin rashes). Repeated contact may result in persistent chronic palmar/hand dermatitis in a smaller number of individuals, despite efforts to reduce or avoid nickel exposure.

## **Chronic toxicity**

#### a) Oral: No information available

- b) Inhalation: Exposure related toxicities were noted following 13 weeks and two years of exposure to NiO in both rats and mice in the US NTP chronic rat inhalation study. Adverse effects in rodents were primarily limited to the lung (e.g. increased tissue weight, inflammation, macrophage hyperplasia). The LOAEC from the chronic study in rats was
- 0.6 mg NiO/m<sup>3</sup> or 0.5 mg Ni/m<sup>3</sup>
- c) Dermal: No information available

#### Mutagenicity/Reproductive toxicity

Not classified for reproductive/developmental toxicity. Not classified for mutagenecity.

#### Carcinogenicity

- a) Ingestion: No information available. Not classified
- b) Inhalation: Category 1A; Human epidemiological And animal data suggest that at least some forms of nickel oxide can be carcinogenic to the respiratory tract of humans after inhalation.

#### **Cobaltous Oxide**

#### LD50 ORAL RAT 202mg/kg

**Inhalation:** Causes irritation to the respiratory tract, symptoms may include coughing, shortness of breath and nausea. Respiratory hypersensitivity, asthma may appear. Inhalation of cobalt dust and fumes is associated with an increased incidence of lung disease.

**Ingestion:** Causes abdominal pain, nausea, vomiting, flushing of the face and ears, mild hypotension, rash and ringing in the ears.

Skin contact: May cause dermatitis, Causes irritation to skin. Symptoms include redness, itching and pain.

Eye contact: Causes irritation, redness and pain.



**Pre-existing Conditions:** Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance. Persons with allergies or sensitivity to cobalt may also be more susceptible to the effects of the substance.

## Nickel Hydroxide

No information currently available.

\_



according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012 **NICKEL OXIDE** Safety Data Sheet

### **SECTION 12: Ecocological information.**

#### 12.1. Toxicity

Aquatic Chronic 4. May cause long lasting harmful effects to aquatic life.

#### 12.2. Persistence and degradability

The PBT and vPBT criteria of Annex XIII to the Regulation do not apply to inorganic substances, such as nickel metal. The methods for determining the biological degradability are not applicable to inorganic substances.

#### **12.3. Bioaccumulative potential**

Nickel does not tend to bioaccumulate or biomagnify in aquatic or terrestrial systems.

#### 12.4. Mobility in soil

The substance is essentially insoluble in water.

#### 12.5. Results of PBT and vPvB assessment Not

classified as PBT or vPBT.

#### 12.6. Other adverse effects None

anticipated

#### **SECTION 13: Disposal considerations.**

#### 13.1. Waste treatment methods

Recover or recycle if possible. Dispose of contents in accordance with local, national or international legislation

#### **13.2. Additional Information**

No information available



according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012

NICKEL OXIDE Safety Data Sheet

## **SECTION 14: Transport information.**

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

#### 14.1. UN number

Not applicable

#### 14.2. UN proper shipping name

Not classified as dangerous according to Transport Regulations

#### 14.3. Transport hazard class(es)

Not applicable

#### **14.4. Packing group** Not applicable

.....

# 14.5. Environmental hazards

Other information: No supplementary information available.

#### 14.6. Special precautions for user

# 14.6.1. Overland transport

Not applicable **14.6.2. Transport by sea** No additional information available

#### **14.6.3. Air transport** No additional information available

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable



according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012

## **SECTION 15: Regulatory information.**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. Classification according to Dangerous Substance Directive

67/548EEC T – Toxic: Category 1 carcinogen.

R48/23: Toxic: danger of serious damage to health by prolonged exposure through inhalation R49:

May cause cancer by inhalation

R43: May cause sensitisation by skin contact

R53: May cause long-term adverse effects in the aquatic environment

S53: Avoid exposure - obtain special instructions before use

S45: In case of accident or if you feel unwell seek medical advice immediately (show the label where possible) S61: Avoid release to the environment. Refer to special instructions/safety data sheet

—

# NICKEL OXIDE Safety Data Sheet

All components are listed on EINECS. (European Inventory of Existing Chemical Substances)

#### 15.1.2. Classification according to Part 3 of Annex VI of EU Regulations No. 1272/2008

Skin Sensitization: Category 1 Carcinogenicity: Category 1A Specific Target Organ Toxicity, Repeated exposure: Category 1 Aquatic Chronic: Category 4

Symbols: GHS07 – Exclamation mark GHS08 – Health Hazard





according to Regulation (EC) No. 1907/2006 (REACH) & 1272/2008 (CLP) Date of issue: 22/12/2010 Revision date: 12/12/2012

Signal Word: DANGER

Hazard Statements H317: May cause an allergic skin reaction H350: May cause cancer H372: Causes damage to organs through prolonged or repeated exposure H413: May cause long lasting harmful effects to aquatic life Precautionary Statements Prevention: P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P260: Do not breathe dust/fume/gas/mist/vapours/spray. P261: Avoid breathing dust/fume/ gas/mist/vapours/spray. P264: Wash hands and face thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P272: Contaminated work clothing should not be allowed out of the workplace P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection. P281: Use personal protective equipment as required

Response:

P302+P352: IF ON SKIN: Wash with plenty of water

P308+P311: IF exposed or concerned Get medical advice/attaention

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

-



# NICKEL OXIDE

Safety Data Sheet

P314: Get Medical advice/attention if you feel unwell.P321: See Safety Data Sheet for specific treatment P363:Wash contaminated clothing before reuse.

Storage: P405: Store locked up

Disposal: P501: Dispose of contents/container in accordance with local/regional/national/international regulations

# SECTION16:Otherinformation.

## 16.1. Indications of change

a) Original Document

b) Formatting Changes

The following Acronyms may be found in this document ACGIH: American Conference of Governmental Industrial Hygienists DNEL: Derived No Effect Level LTEL: Long Term Exposure Limit LR: Lead Registrant MMAD: Mass Median Aerodynamic Diameter NIOSH: National Institute of Occupational Safety and Health OEL: Occupatioal Exposure Limits OR: Only Representative OSHA: Occupational Safety and Health Administration PBT: PBT: Persistent, Bioaccumulative and Toxic PNEC: Predicted No Effect Concentration STEL: Short Term Exposure Limit STOT: Specific Target Organ Toxicity TLV - TWA: Threshold Limit Value – Time Weighted Average

vPvB: Very persistent and very Bioaccumulative WEL: Workplave Exposure Limit (UK HSE EH40)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

DISCLAIMER OF LIABILITY The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding



its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable

SDS Ref:- 12-12-2014